

## REFLUX EXTRACTOR (A-035)

ASTM D2172 • AASHTO T-164

- Used to determine the percentage of bitumen in the asphalt pavement mixtures.
- Equipped with a glass cylinder, two wire mesh cones and brass condenser.
- Filter Papers should be ordered separately



Reflux Extractor (A-035)

### TECHNICAL SPECIFICATIONS

- Capacity: 1000 g / 4000 g
- Glass Jar Cylinder
- Wire mesh Cone (2 ea)
- Thermometer
- Hotplate
- Brass Condenser

| Code    | Capacity (g) |
|---------|--------------|
| A-035/1 | 1000         |
| A-035/4 | 4000         |

## CENTRIFUGE - EXTRACTOR (A-031)

ASTM D2172 • AASHTO T-164

- Used to determine the bitumen percentage in the asphalt mixtures.
- The extractor is available in two capacities (1500 g and 3000 g), and it is equipped with a speed control knob.
- Filter Papers should be ordered separately



Centrifuge - Extractor (A-031)

### TECHNICAL SPECIFICATIONS

- Capacity: 1500 g / 3000 g
- Speed control knob
- Brake for fast stopping
- Filter Papers should be ordered separately
- Power Supply: 220 - 240 V / 50 or 60 Hz (110 V / 60 Hz is also available)

| Code     | A-031/15 | A-031/30 |
|----------|----------|----------|
| Capacity | 1500 g   | 3000 g   |